

## Billerud Pure Decor™ LINER

### Product Description

The light coated Pure Decor™ kraftliner is a preferred material for high quality post-print and pre-print. High strength ensures light, strong packages with minimised washboarding. Pure Decor™ is produced from 100% virgin fibres.

### Basis weight

30, 33, 36 lb / 1000ft<sup>2</sup>

### Approvals

Pure Decor™ is produced in compliance with FDA and BfR packaging norms.

### Certification

Production is certified in accordance with ISO 9001, ISO 14001, ISO 50001 and FSSC 22000.

Property	Unit		Method		
Basis weight	lb / 1000ft <sup>2</sup>	30	33	36	ISO 536
Caliper	in / 1000	7,1	7,7	8,3	ISO 534
Scott Bond	in*lb / in <sup>2</sup>	2,0	2,0	2,0	TAPPI T569
Burst strenght	psi	102	113	123	ISO 2759
SCT	CD lbf / in	18,3	20,5	22,8	ISO 9895
Tensile	MD lbf / in	6850	7420	7990	ISO 1924
Stiffness	CD lbf / in	3425	3995	4565	
Roughness PPS-10	PS μm	1,4	1,5	1,6	ISO 8791-4
Gloss	PS %	42	42	42	TAPPI T480
Brightness	PS %	80	80	80	ISO 2470
Whiteness D65	PS %	81	81	81	ISO 11475
Cobb	PS lb / 1000ft <sup>2</sup>	7,0	7,0	7,0	ISO 535
	RS lb / 1000ft <sup>2</sup>	7,8	7,8	7,8	
Moisture	%	7,0	7,0	7,0	ISO 287

MD = Machine Direction CD = Cross Direction PS = Print Side RS = Reverse Side Test climate: 50% RH, 23°C

The table shows typical data for a range of grammages.

Rev. 202402